

Product information

FIRESTOP PUTTY DISC CFS-D 1"

Product description

- · Self-adhesive discs of firestop putty for single cables and bundles
- in openings up to 1"

Applications for use

- Low-voltage cables: telephone, Ethernet (up to CAT 6), fiber optic,coax RG 6 and emergency cables
- Suitable for electrical metal tubing and rigid or flexible steel conduits
- Small pipe penetrations: PE, copper, steel and cast iron
- Mid-voltage cables: Romex®, metal-clad and power cables
- General gypsum wall assemblies with wood or metal studs
- Suitable for membrane or complete through-penetrations

Advantages

- Faster installed in 10 seconds: peel, stick, done!
- Simple, sealant-free installation
- Surface-mounted solution
- Applied by hand, no tools required. Disc can be molded without leaving residue on hands
- No backfilling material required
- Tested for electrical conductivity
- Low VOCs to meet LEED™ requirements for indoor environmental quality
- Red list and Living Building Challenge (LBC) compliant
- Asbestos, formaldehyde and LABS free

Installation instructions

See Hilti literature or third-party listings for complete application and installation details







Order designation	Sales pack quantity	ltem number
CFS-D 1"	32	2116254
CFS-D 1" (24 boxes)	768	3549770
CFS-D 1" (48 boxes)	1536	3549771

Technical Data


Mold-able putty	
Red	
32° to 104°F (0° to 40°C)	
23° to 104°F (-5° to 40°C)	
-4° to 104°F (-20° to 40°C)	
1.6 g/cm ³	
Class 0 (ASTM G21-96)	
UL 1479, CAN/ULC-S115, ASTM E814	
Flame Spread 0 Smoke Development 5	
Yes	
12.18 g/L	
32 pcs per box	
62 (relates to specific construction) ASTM E90	
Not relevant	
up to 100% per tested system	





Mold and mildew Sou resistant

isolation



Sr



