

Firestop collar CP 643 N




Applications

- Plastic pipes with diameters from 32 - 170 mm
- Suitable for PVC, HDPE, PP and ABS pipes

Advantages

- Latch mechanism for quick and easy closure
- Allows correct installation in situations where space is tight
- Flexible tab positioning for convenient fastening
- Ready-to-use product



Technical data

Base materials	Concrete, Drywall, Masonry
Expansion temperature (approx.)	250 °C
Intumescent	Yes
Storage and transportation temperature range	-5 - 50 °C
Application temperature range	-5 - 50 °C
Temperature resistance range	-20 - 100 °C
Tested in accordance with	UL 1479, CAN/ULC-S115, ASTM E814, ASTM G21, ETA
LEED VOC	7.6 g/l
Complementary products	CP 643/644 Fastening hook
Acoustic insulation	No



Ordering designation	Pipe diameter - range	Outside diameter	Height	Sales pack quantity	Item number
CP 643-50/1.5" N	32 - 51 mm	67 mm	22 mm	1 pc	304325
CP 643-63/2" N	52 - 64 mm	82 mm	32 mm	1 pc	304326
CP 643-90/3" N	79 - 91 mm	116 mm	42 mm	1 pc	304328
CP 643-110/4" N	92 - 115 mm	146 mm	47 mm	1 pc	304329

Please visit our website for the latest item numbers and related products.