

**Firestop collar CP 644**




**Applications**

- Sealing flammable pipes from 32mm to 250mm in diameter in penetrations through fire compartment walls and floors

**Advantages**

- Ready-to-use firestop collar with a galvanized steel housing
- Latch mechanism for quick and easy closure
- Flexible hook positioning for convenient fastening



**Technical data**

<b>Base materials</b>	Concrete, Drywall, Masonry
<b>Expansion temperature (approx.)</b>	210 °C
<b>Intumescent</b>	Yes
<b>Storage and transportation temperature range</b>	-5 - 50 °C
<b>Application temperature range</b>	-5 - 50 °C
<b>Temperature resistance range</b>	-20 - 100 °C
<b>Tested in accordance with</b>	UL 1479, ETA
<b>LEED VOC</b>	7.6 g/l
<b>Complementary products</b>	CP 643/644 Fastening hook
<b>Acoustic insulation</b>	No



Firestop Systems and Construction Chemicals

Ordering designation	Pipe diameter - range	Outside diameter	Height	Sales pack quantity	Item number
CP 644-180/7"		228 mm	153 mm	1 pc	304339
CP 644-200/8"		257 mm	178 mm	1 pc	304340
CP 644-225/9"		289 mm	203 mm	1 pc	304342
CP 644-250/10"		319 mm	233 mm	1 pc	304343
CP 644-50/1.5"	32 - 51 mm	67 mm	22 mm	1 pc	304332
CP 644-63/2"	52 - 64 mm	82 mm	32 mm	1 pc	304333
CP 644-90/3"	79 - 91 mm	117 mm	42 mm	1 pc	304335
CP 644-110/4"	92 - 115 mm	146 mm	47 mm	1 pc	304336
CP 644-125/5"	116 - 125 mm	166 mm	48 mm	1 pc	304337
CP 644-160/6"	126 - 170 mm	236 mm	48 mm	1 pc	304338

Please visit our website for the latest item numbers and related products.