

### Firestop speed sleeve CP 653




#### Applications

- Sealing penetrations with single cables and cable bundles
- Suitable for small to medium-sized circular openings in walls, ceilings and floors
- For use on concrete, masonry and drywall

#### Advantages

- Easy and fast to install and to inspect
- Fully functional immediately after installation
- Robust
- Optimum smoke-restriction performance
- Easy maintenance and retro-fitting of cables
- Fire resistance rating of up to 2 hours



#### Technical data

<b>Base materials</b>	Concrete, Masonry, Drywall
<b>Expansion temperature (approx.)</b>	160 °C
<b>Intumescent</b>	Yes
<b>Storage and transportation temperature range</b>	-5 - 50 °C
<b>Application temperature range</b>	-5 - 50 °C
<b>Temperature resistance range</b>	-30 - 100 °C
<b>Approvals</b>	FM,UL
<b>Tested in accordance with</b>	ASTM E814, UL 1479, CAN/ULC-S115, UL 2043, ASTM G21, ETA
<b>Reusable (and removable)</b>	Possible
<b>Acoustics performance</b>	Test report available



Ordering designation	Sales pack quantity	Item number
CP 653 2"	1 pc	236323
CP 653 4"	1 pc	236324 <sup>1)</sup>

<sup>1)</sup> This is a non-stock item. For detailed lead time information please contact your Hilti representative.

Please visit our website for the latest item numbers and related products.