

## OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on May 28, 2013.

Hilti AG Feldkircherstrasse 100 FL-9494 Liechtenstein 423 234 2111

Facility: Kaufering, Germany

		Joining and Sealing Materials		
			Water	Water Contact
Trade Designation		Size	Temp	Material
Adhesives				
Hilti HIT-CT 1 <sup>[2]</sup>		NA	CLD 23	ADH
Hilti HIT-HY 150 <sup>[2]</sup>		NA	CLD 23	ADH
Hilti HIT-HY 150 Adhesive Anchoring System	[2]	NA	CLD 23	ADH
Hilti HIT-HY 150 Max <sup>[2]</sup>		NA	D. HOT	ADH
Hilti HIT-HY 150 Max Adhesive Anchoring System	[2]	NA	D. HOT	ADH
Hilti HIT-HY 150 Max-SD <sup>[2]</sup>		NA	D. HOT	ADH
Hilti HIT-RE 500 <sup>[2]</sup>		NA	D. HOT	EPOXY
Hilti HIT-RE 500 Adhesive Anchoring System	[2]	NA	D. HOT	EPOXY
Hilti HIT-RE 500 SD <sup>[2]</sup>		NA	D. HOT	EPOXY
Hilti HIT-RE 500 SD Adhesive Anchoring System	[2]	NA	D. HOT	EPOXY
Hilti HIT-HY 150-FR <sup>[2]</sup>		NA	CLD 23	ADH
Hilti HIT-HY 150-FR Adhesive Anchoring System		NA	CLD 23	ADH
Hilti HVU Anchoring Adhesive	2]	NA	CLD 23	ADH
HIT-HY200 <sup>[1]</sup>		NA	D. HOT	ADH
HIT-HY200-A <sup>[1]</sup>		NA	D. HOT	ADH
HIT-HY200-R <sup>[1]</sup>		NA	D. HOT	ADH

<sup>[1]</sup> Certified for use as an anchoring adhesive for installing threaded rods (less than or equal to 32 mm in diameter) in concrete for water treatment applications.

<sup>[2]</sup> Product is Certified for use as an anchoring adhesive for installing threaded rods (less than or equal to 1.3 inches in diameter) in concrete for water treatment applications.

	Mechanical Devices		
Trade Designation	Size	Water Contact Temp	Water Contact Material
Miscellaneous Process Devices/Components			
HVA Adhesive Anchoring System	3/8" - 1 1/4"	CLD 23	MLTPL

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International. 1 of 1